Visualization of a blood flow with Two-Dimensional Moving Target Indication

Tsuyoshi KIMURA, Osamu OSHIRO, Ayumu MATANI,
Kosuke SATO and Kunihiro CHIHARA

Graduate School of Information Science, Nara Institute of Science and Technology.

1 Introduction

Since the appearance of a sonar in World War I, ultrasonic devices are widely spread and applied for various fields; non-destructive evaluations for industrial field, fish finders for fishery, active sonars for military use and diagnostic devices for clinical use. An ultrasonic diagnostic device has been a powerful tool to observe organs such as heart, liver, and so on and fetus with scanning an ultrasonic beam for the last two decades.

A current ultrasonic diagnostic device has the function not only to observe the morphology of organs but also to visualize a blood flow based on Doppler effect at the same time. However, owing to the disadvantage of Doppler effect, only the component parallel to an ultrasonic beam can be detected. Therefore, the detailed observation of the blood flow is not performed, especially, in the neighborhood of valves of a heart.

In order to measure a blood velocity vector, the Doppler frequency shift must be detected from three different directions. Chihara et al.[1] and Fox et al.[2] developed three-probe ultrasonic Doppler systems to measure the blood velocity vector at one point. However, the three-probe systems can not measure a blood velocity profiles at many points, because it is difficult to scan and to focus three beams in a human heart. Otsuki et al.[3] presented a method, based on the assumption that a flow direction is restricted to a 2-D plane, for estimating 2-D blood velocity vectors in a human heart by using the conventional color Doppler system and Euler's equation in flow dynamics. Furthermore, Chihara et al.[4] proposed a similar method using an equation of continuity in place of Euler's equation. Since the blood flow is not restricted to the 2-D plane, however, these estimation methods can not obtain the exact projection of the three-dimensional blood velocity vector on the 2-D plane.

As a new method to measure the blood flow instead of ultrasonic Doppler method overcoming problems as described above, we proposed High-speed Digital Subtraction Echography(High-speed DSE) and Two-Dimensional Moving Target Indication(2D-MTI) method [5]-[8] to visualize the blood flow and successed in extracting particles. The DSE method has existed from long ago and not been used for ultrasonic images. It was unsuitable for extraction of moving targets, because old type of the ultrasonic diagnostic device could be taken in only row frame rates.